SAFETY DATA SHEET

Mercasol 9 high penetrating primer

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name
Mercasol 9 high penetrating primer

Product no.
42430

Unique formula identifier (UFI)
HM42-30HS-X001-XMXG

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture
Corrosion inhibitor
Restricted to professional users.

Use descriptors (UK REACH)

Sectors of use	Description
LCS "C"	Consumer uses: Private households (= general public = consumers)
LCS "PW"	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category	Description
PC 14	Metal surface treatment products, including galvanic and electroplating products

Uses advised against
None known.

1.3. Details of the supplier of the safety data sheet

▼Company and address

Auson AB
Verkstadsgatan 3
S-434 42 KUNGSBACKA
Sweden
+46 (0)300 56 20 00

Contact person
Nina Nyth

E-mail
nina.nyth@auson.se

Revision
13/05/2025

SDS Version
5.0

Date of previous version
01/11/2024 (4.0)

1.4. Emergency telephone number

Healthcare professionals: Dial 0344 892 0111 to reach The National Poisons Information Service (NPIS) (24 hour service)
General public:
England - Dial 111 to reach NHS 111 (24 hour service)
Scotland - Dial 112 to reach NHS 24 (24 hour service)
Wales - Dial 111 or 0845 4647 to reach NHS Direct (24 hour service)
See section 4 “First aid measures”.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Flam. Liq. 3; H226, Flammable liquid and vapour.
Asp. Tox. 1; H304, May be fatal if swallowed and enters airways.
Skin Sens. 1; H317, May cause an allergic skin reaction.

STOT SE 3; H336, May cause drowsiness or dizziness.
Aquatic Chronic 3; H412, Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

Flammable liquid and vapour. (H226)
May be fatal if swallowed and enters airways. (H304)
May cause an allergic skin reaction. (H317)
May cause drowsiness or dizziness. (H336)
Harmful to aquatic life with long lasting effects. (H412)

Precautionary statement(s)

General

Keep out of reach of children. (P102)

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)
Avoid breathing mist/vapour. (P261)
Use only outdoors or in a well-ventilated area. (P271)
Wear eye protection/protective gloves/protective clothing. (P280)

Response

IF SWALLOWED: Immediately call a POISON CENTER/doctor. (P301+P310)
IF ON SKIN: Wash with plenty of water and soap. (P302+P352)
IF INHALED: Remove person to fresh air and keep comfortable for breathing. (P304+P340)

Storage

Store locked up. (P405)

Disposal

Dispose of contents/container in accordance with local regulation
(P501)

Hazardous substances

Hydrocarbons, C9-C10, n-alcane, isoalkane, cyclene, < 2% aromatics
Destillate (petroleum), solventdewaxed heavy naphthenic (<3% DMSO)

Additional labelling

EUH066, Repeated exposure may cause skin dryness or cracking.

UFI: HM42-30HS-X001-XMXG
Tactile warning: Yes.

VOC

VOC content: 628 g/L
MAXIMUM VOC CONTENT (Phase II, category B/e: 840 g/L)

2.3. Other hazards

Additional warnings

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.
This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Hydrocarbons, C9-C10, n-alcane, isoalkane, cyclene, < 2% aromatics	CAS No.: 64742-48-9 EC No.: 927-241-2 UK-REACH: Index No.:	75 -80 %	EUH066 Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 3, H412	[19]
Destillate (petroleum),	CAS No.: 64742-65-0	8 -10 %	Asp. Tox. 1, H304	[19]

solventdewaxed heavy naphthenic (<3% DMSO)	EC No.: 265-169-7 UK-REACH: Index No.:			
Phosphoric acid, C8-16-alkyl esters, reaction products with (Z)-N-9-octadecenyl-1,3-propanediamine	CAS No.: 90506-47-1 EC No.: 291-909-3 UK-REACH: Index No.:	~ 5 %	Skin Irrit. 2, H315 Eye Irrit. 2, H319	
Calcium sulfonate	CAS No.: 61789-86-4 EC No.: 263-093-9 UK-REACH: Index No.:	2 -3 %	Skin Sens. 1B, H317	[19]
Sulfonic acids, petroleum, sodium salts	CAS No.: 68608-26-4 EC No.: 271-781-5 UK-REACH: Index No.:	1 -2 %	Eye Irrit. 2, H319	[19]

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet.
Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.
If skin irritation occurs: Get medical advice/attention.

Eye contact

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during transport.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER/doctor.
Do not induce vomiting! If vomiting occurs, keep head facing down so that vomit does not get into the lungs. Call a doctor or ambulance. Symptoms of chemical pneumonia can appear after several hours. People who have swallowed the product should therefore be kept under medical attention for at least 48 hours.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

This product contains substances that can cause chemical pneumonia if swallowed. Symptoms of chemical pneumonia may appear after several hours.
Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact.
Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:
Get immediate medical advice/attention.
If skin irritation or rash occurs: Get medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media
Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.
Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture
Flammable liquid and vapour.
In use may form flammable/explosive vapour-air mixture.
Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

5.3. ▼Advice for firefighters
Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.
Hazchem Code: ●3Y

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.
Avoid direct contact with spilled substances.
Ensure adequate ventilation, especially in confined areas.
Avoid inhalation of vapours from spilled material.
Contaminated areas may be slippery.

6.2. Environmental precautions
Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up
Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.
Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections
See section 13 “Disposal considerations” on handling of waste.
See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling
Ground and bond container and receiving equipment.
Use explosion-proof [electrical/lighting/ventilating] equipment.
Use non-sparking tools.
Take action to prevent static discharges.
It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.
Avoid direct contact with the product.
Smoking, drinking and consumption of food is not allowed in the work area.
See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities
Containers that have been opened must be carefully resealed and kept upright to prevent leakage.
Take action to prevent static discharges.
Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Recommended storage material
Always store in containers of the same material as the original container.

Storage conditions
No specific requirements

Incompatible materials
Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)
This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No substances are listed in the national list of substances with an occupational exposure limit.

DNEL

Calcium sulfonate

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Dermal	513 µg/cm²
Long term – Local effects - Workers	Dermal	1.03 mg/cm²
Long term – Systemic effects - General population	Dermal	1.667 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	3.33 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	2.9 mg/m³
Long term – Systemic effects - Workers	Inhalation	11.75 mg/m³
Long term – Systemic effects - General population	Oral	833.3 µg/kg bw/day

Destillate (petroleum), solventdewaxed heavy naphthenic (<3% DMSO)

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - Workers	Dermal	970 µg/kg bw/day
Long term – Local effects - General population	Inhalation	1.19 mg/m³
Long term – Local effects - Workers	Inhalation	5.58 mg/m³
Long term – Systemic effects - Workers	Inhalation	2.73 mg/m³
Long term – Systemic effects - General population	Oral	740 µg/kg bw/day

Hydrocarbons, C9-C10, n-alcane, isoalkane, cyclene, < 2% aromatics

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	178.57 mg/m³
Long term – Local effects - Workers	Inhalation	837.5 mg/m³
Long term – Systemic effects - General population	Inhalation	410 µg/m³
Long term – Systemic effects - Workers	Inhalation	1.9 mg/m³
Short term – Local effects - General population	Inhalation	640 mg/m³
Short term – Local effects - Workers	Inhalation	1066.67 mg/m³
Short term – Systemic effects - General population	Inhalation	1152 mg/m³
Short term – Systemic effects - Workers	Inhalation	1286.4 mg/m³

Sulfonic acids, petroleum, sodium salts

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	1.667 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	3.33 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	330 µg/m³
Long term – Systemic effects - Workers	Inhalation	660 µg/m³
Long term – Systemic effects - General population	Oral	833.3 µg/kg bw/day

PNEC

Calcium sulfonate

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		1 mg/L
Freshwater sediment		226000000 mg/kg
Intermittent release (freshwater)		10 mg/L
Marine water		1 mg/L
Marine water sediment		226000000 mg/kg
Predators		16.667 mg/kg
Sewage treatment plant		1 g/L
Soil		271000 g/kg

Destillate (petroleum), solventdewaxed heavy naphthenic (<3% DMSO)

Route of exposure:	Duration of Exposure:	PNEC:
Predators		9.33 mg/kg

Sulfonic acids, petroleum, sodium salts

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		1 mg/L
Freshwater sediment		723500000 mg/kg
Intermittent release (freshwater)		10 mg/L
Marine water		1 mg/L
Marine water sediment		723500000 mg/kg
Predators		16.667 mg/kg
Sewage treatment plant		100 mg/L
Soil		868700 g/kg

8.2. Exposure controls

Apply general control to prevent unnecessary exposure

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Occupational exposure limits have not been defined for the substances in this product.

Appropriate technical measures

Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

Generally

Use only UKCA marked protective equipment.

Respiratory Equipment

Type	Class	Colour	Standards
Respiratory protection is not needed in the event of adequate ventilation.			

Skin protection

Recommended	Type/Category	Standards
Wear appropriate protection clothing, e.g. coveralls in polypropylene or working clothes in cotton or polyester.	-	-



▼Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
Nitrile	0,38	> 480	EN374-2, EN16523-1, EN388



Eye protection

Type	Standards
Safety glasses	EN166



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state
Liquid

Colour
Red

Odour / Odour threshold
Solvent

pH
Not applicable - pH is not defined for non-aqueous systems

Density (g/cm^3)
0,77-0,83 (20 °C)

Kinematic viscosity
<20,5 mm^2/s (40 °C)

Particle characteristics
Not applicable - product is a liquid

Phase changes

Melting point/Freezing point (°C)
No data available

Softening point/range (°C)
Does not apply to liquids.

Boiling point (°C)
140 -170

Vapour pressure
0.5 kPa (20 °C)

Relative vapour density
4,5

Decomposition temperature (°C)
Not applicable - product is an article

Data on fire and explosion hazards

Flash point (°C)
32

Flammability (°C)
The material is ignitable.

Auto-ignition temperature (°C)
>200

Lower and upper explosion limit (% v/v)
0.8 - 6

Solubility

Solubility in water
Insoluble

n-octanol/water coefficient (LogKow)
> 4

▼Solubility in fat (g/L)
No data available.

9.2. Other information

VOC (g/l)
628

Oxidizing properties
Non-oxidizing

Other physical and chemical parameters
No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity
No data available.

10.2. Chemical stability
The product is stable under the conditions, noted in section 7 “Handling and storage”.

10.3. Possibility of hazardous reactions
None known.

10.4. Conditions to avoid
Avoid static electricity.
Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials
Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. ▼Hazardous decomposition products
Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 as retained and amended in UK law

▼Acute toxicity

Product/substance	Hydrocarbons, C9-C10, n-alcane, isoalkane, cyclene, < 2% aromatics
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	> 5000 mg/kg

Product/substance	Hydrocarbons, C9-C10, n-alcane, isoalkane, cyclene, < 2% aromatics
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	> 5000 mg/kg

Product/substance	Hydrocarbons, C9-C10, n-alcane, isoalkane, cyclene, < 2% aromatics
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	> 5000 mg/m³

Product/substance	Destillate (petroleum), solventdewaxed heavy naphthenic (<3% DMSO)
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	> 5000 mg/kg

Product/substance	Destillate (petroleum), solventdewaxed heavy naphthenic (<3% DMSO)
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	> 5,5 mg/l

Product/substance	Destillate (petroleum), solventdewaxed heavy naphthenic (<3% DMSO)
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	> 2000 mg/kg

Product/substance	Sulfonic acids, petroleum, sodium salts
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	> 2000 mg/kg

Product/substance	Sulfonic acids, petroleum, sodium salts
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	> 5000 mg/kg

Product/substance	Sulfonic acids, petroleum, sodium salts
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50

Result: > 1,9 mg/l

Based on available data, the classification criteria are not met.

Skin corrosion/irritation
Based on available data, the classification criteria are not met.

Serious eye damage/irritation
Based on available data, the classification criteria are not met.

Respiratory sensitisation
Based on available data, the classification criteria are not met.

Skin sensitisation
May cause an allergic skin reaction.

Germ cell mutagenicity
The chemical structure does not suggest a mutagenic effect.

Carcinogenicity
Does not present any cancer hazards.

Reproductive toxicity
The chemical structure does not suggest such an effect.

STOT-single exposure
May cause drowsiness or dizziness.

STOT-repeated exposure
Based on available data, the classification criteria are not met.

Aspiration hazard
May be fatal if swallowed and enters airways.
Aspiration may cause chemical pneumonitis.

11.2. Information on other hazards

Long term effects
None known.

▼Endocrine disrupting properties
This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information
None known.

SECTION 12: Ecological information

12.1. Toxicity

Product/substance	Hydrocarbons, C9-C10, n-alcane, isoalkane, cyclene, < 2% aromatics
Species:	Fish
Duration:	No data available.
Result:	10 - 30 mg/L

Product/substance	Hydrocarbons, C9-C10, n-alcane, isoalkane, cyclene, < 2% aromatics
Species:	Algae
Duration:	No data available.
Result:	> 1000 mg/L

Product/substance	Hydrocarbons, C9-C10, n-alcane, isoalkane, cyclene, < 2% aromatics
Species:	Crustacean
Duration:	No data available.
Result:	22 - 46 mg/L

Product/substance	Destillate (petroleum), solventdewaxed heavy naphthenic (<3% DMSO)
Species:	Fish, Oncorhynchus mykiss
Duration:	No data available.
Test:	LC50
Result:	> 100 mg/l

Product/substance	Destillate (petroleum), solventdewaxed heavy naphthenic (<3% DMSO)
Species:	Algae, Pseudokirchneriella subcapitata
Duration:	No data available.
Test:	NOEC
Result:	> 100 mg/l

Product/substance	Sulfonic acids, petroleum, sodium salts
Species:	Fish

Duration:	No data available.
Test:	LC50
Result:	> 10000 mg/l

Product/substance	Sulfonic acids, petroleum, sodium salts
Species:	Algae
Duration:	No data available.
Test:	ERC50
Result:	> 1000 mg/l

Product/substance	Sulfonic acids, petroleum, sodium salts
Species:	Crustacean, Daphnia magna
Duration:	No data available.
Test:	EC50
Result:	> 1000 mg/l

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability
Based on available data, the classification criteria are not met.

12.3. Bioaccumulative potential
Based on available data, the classification criteria are not met.

12.4. Mobility in soil
No data available.

12.5. Results of PBT and vPvB assessment
This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Endocrine disrupting properties
This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects
This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: Disposal considerations

▼Waste treatment methods
Product is covered by the regulations on hazardous waste. (*)
HP 3 - Flammable
HP 5 - Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP 14 – Ecotoxic
Dispose of contents/container to an approved waste disposal plant.
Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

EWC code
13 02 05* Mineral-based non-chlorinated engine, gear and lubricating oils

Specific labelling

Contaminated packing
Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	UN1139	COATING SOLUTION	Transport hazard class: 3 Label: 3 Classification code: F1 	III	No	Limited quantities: 5 L Tunnel restriction code: (D/E) See below for additional information.

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
IMDG	UN1139	COATING SOLUTION	Transport hazard class: 3 Label: 3 Classification code: F1 	III	No	Limited quantities: 5 L EmS: F-E S-E See below for additional information.
IATA	UN1139	COATING SOLUTION	Transport hazard class: 3 Label: 3 Classification code: F1 	III	No	See below for additional information.

* Packing group

** Environmental hazards

Additional information

This product is within scope of the regulations of transport of dangerous goods.
ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.
IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.
IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.
Hazchem Code: ●3Y

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

Restricted to professional users.
People under the age of 18 shall not be exposed to this product.

Demands for specific education

No specific requirements.

Control of Major Accident Hazards (COMAH) - Categories / dangerous substances

P5c - FLAMMABLE LIQUIDS, Qualifying quantity (lower-tier): 5.000 tonnes / (upper-tier): 50.000 tonnes

UK-REACH, Annex XVII

Hydrocarbons, C9-C10, n-alcane, isoalkane, cyclene, < 2% aromatics is subject to UK-REACH restrictions (entry 40).

Additional information

Not applicable.

Sources

The Management of Health and Safety at Work Regulations 1999.
Control of Major Accident Hazards (COMAH) Regulations 2015.
2012 No. 1715 ENVIRONMENTAL PROTECTION: The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012.
Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.
Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.
Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

EUH066, Repeated exposure may cause skin dryness or cracking.
H226, Flammable liquid and vapour.
H304, May be fatal if swallowed and enters airways.
H315, Causes skin irritation.
H317, May cause an allergic skin reaction.
H319, Causes serious eye irritation.
H336, May cause drowsiness or dizziness.
H412, Harmful to aquatic life with long lasting effects.

The full text of identified uses as mentioned in section 1

LCS "C" = Consumer uses: Private households (= general public = consumers)
LCS "PW" = Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
PC 14 = Metal surface treatment products, including galvanic and electroplating products

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CE = Conformité Européenne (European conformity)
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
CSA = Chemical Safety Assessment
CSR = Chemical Safety Report
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EINECS = European Inventory of Existing Commercial chemical Substances
ES = Exposure Scenario
EUH statement = CLP-specific Hazard statement
EuPCS = European Product Categorisation System
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
GWP = Global warming potential
IARC = International Agency for Research on Cancer (IARC)
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.
The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.
The classification of the mixture in regard to physical hazards has been based on experimental data.

The safety data sheet is validated by

Nina Nyth

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.
The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.
It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.
Country-language: GB-en